



**GLOBAL
GRAB**

SW1900 Wedge



About

Global GRAB's SW1900 Wedge Barrier is well known to hostile vehicle and perimeter security global professionals as being a proven and reliable active vehicle barrier system, engineered and manufactured to withstand high impact passenger and cargo vehicle impacts for government and commercial organizations. The SW1900 is designed with an innovative noise-dampening technology that is well-suited for installations near businesses or other properties that are sensitive to noise levels. To make the installation fast and cost effective, the shallow (18" foundation) mount barrier is shipped in one piece.

To further demonstrate the best-in-class capabilities, durability, and value of Global GRAB's SW1900 Wedge Barrier, following an independent third-party vehicle crash-testing of the SW1900; after the crash-test wreckage was removed, the SW1900 was immediately cycled multiple times under its own power demonstrating that the SW1900 could withstand an impact and remain functional, as compared to some wedge barrier systems that would need to be immediately replaced.

© Copyright Global GRAB Technologies. All Rights Reserved.



277 Mallory Station Road
Suite 112 Franklin, TN 37067



info@grabglobal.com



General Inquiries: **615.224.0400**
24/7 Support: **866.504.4722**



**GLOBAL
GRAB**

SW1900 Wedge

Certified Security

The SW1900 Wedge Barrier is ASTM M50/P1 Crash Certified, U. S. Department of Homeland Security SAFETY Act Certified as an "Approved Product for Homeland Security" and is on the DoD Anti-Ram Barrier List.



Two Lane SW1900 Wedge Barrier System



SW1900 Wedge Barrier System



SW1900 Impact

SW1900 Wedge Specs

- Certified to ASTM M50 P1 Standards
- Electro-Mechanical or Hydraulic Actuation With Identical Certified Barrier Structure
- Noise-Dampening Technology
- 18" Shallow-Mount Foundation
- Easy Installation - One-Day Installation and Ready to Install as Shipped
- No Concrete Required Inside Barrier
- Access Panels That Allow Service and Component Replacement Without Raising the Barrier
- Available in 9' to 16' Widths
- NEMA Rated Control Enclosures
- Pre-Plumbed Drains and Control Pathways Designed Not to Interfere With Rebar Placement
- Standard Feature With All Models EFO Capability

© Copyright Global GRAB Technologies. All Rights Reserved.